

SG60KTL

String Inverter



High Yield

- Max. efficiency 98.9 %, European efficiency 98.7 %
- Long-term overload at 1.1 P_n
- Full power operation without derating at 50 °C



Easy O&M

- Compact design and light weight for easy installation
- Plug-in design of fan and SPD, convenient for on-site maintenance
- Integrated string current monitoring function for fast trouble shooting



Saved Investment


- Max. DC/AC ratio up to 1.4
- Integrated DC combiner box and DC/AC overvoltage protection




Grid Support

- Compliance with standards: IEC 62109, IEC 61727, IEC 62116, VDE0126-1-1, G59/3, VDE-AR-N-4105, VDE-AR-N-4120, BDEW
- Low/High voltage ride through (L/HVRT)
- Active & reactive power control and power ramp rate control

Circuit Diagram



Efficiency Curve



Input (DC)	SG60KTL
Max. PV input voltage	1000 V
Min. PV input voltage / Startup input voltage	570 V / 620 V
Nominal input voltage	710 V
MPP voltage range	570 – 950 V
MPP voltage range for nominal power	570 – 850 V
No. of independent MPP inputs	1
Max. number of PV strings per MPPT	14
Max. PV input current	120 A
Max. current for input connector	12 A
Max. DC short-circuit current	140 A
Output (AC)	
Nominal AC power (at 50 °C)	60000 W
Max. AC output power at PF=1 (at 45 °C)	66000 W
Max. AC apparent power (at 45 °C)	66000 VA
Max. AC output current	96 A
Nominal AC voltage	3 / N / PE or 3 / PE, 230 / 400 V
AC voltage range	310 – 480 V
Nominal grid frequency / Grid frequency range	50 Hz / 45 – 55 Hz, 60 Hz / 55 – 65 Hz
THD	< 3 % (at nominal power)
DC current injection	< 0.5 % I _n
Power factor at nominal power / Adjustable power factor	> 0.99 / 0.8 leading – 0.8 lagging
Feed-in phases / Connection phases	3 / 3
Efficiency	
Max. efficiency / Euro. efficiency	98.9 % / 98.7 %
Protection	
DC reverse connection protection	Yes
AC short-circuit protection	Yes
Leakage current protection	Yes
Grid monitoring	Yes
DC switch / AC switch	Yes / No
DC fuse	Yes (positive, 15A)
PV string current monitoring	Yes
Overvoltage protection	DC Type II / AC Type III
General Data	
Dimensions (W*H*D)	634*959*267 mm
Weight	60 kg
Isolation method	Transformerless
Degree of protection	IP65
Night power consumption	< 1 W
Operating ambient temperature range	-25 to 60 °C (> 50 °C derating)
Allowable relative humidity range (non-condensing)	0 – 100 %
Cooling method	Smart forced air cooling
Max. operating altitude	4000 m (> 3000 m derating)
Display / Communication	Graphic LCD / RS485
DC connection type	MC4 (Max. 6mm ²)
AC connection type	Screw clamp terminal (Max. 95 mm ²)
Compliance	IEC 62109, IEC 61727, IEC 62116, IEC 60068, IEC 61683, VDE0126-1-1, G59/3, VDE-AR-N-4105, VDE-AR-N-4120, BDEW, IEC 61000-3-11/-12, EN 50438, UTE C 15-712-1/07.13, CEA
Grid support	LVRT, HVRT, active & reactive power control and power ramp rate control
Type designation	SG60KTL-182

